PARSCH ROBUST

rubber covered hose with smooth cover

Inner lining:
two-component system consisting of black SBR-rubber and white NBR-adhesive

Exterior:
smooth NBR-rubber

Jacket:
100 % Polyester high tenacity yarn, circular woven, warp threads 2-ply twisted, twill weave

Applications:
industry, construction sites

Characteristics:
extremely high abrasion resistance, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:
cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar	wall thickness mm
19	3/4	170	60	20	1,70
25	1	210	60	20	1,70
32	1 1/4	260	60	20	2,10
38	1 1/2	300	60	20	2,10
42	1 2/3	340	60	20	2,10
45	1 3/4	380	60	20	2,30
52	2	450	50	17	2,30
64	2 1/2	590	50	17	2,30
70	2 3/4	670	50	17	2,60
75	3	720	50	17	2,60
90	3 1/2	920	40	13	3,00
102	4	1010	40	13	3,00
110	4 1/3	1310	35	12	3,00
125	5	1480	30	10	3,00
152	6	1720	30	10	3,00

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.

PARSCH GmbH & Co. KG
Gildestrasse 16, 49477 Ibbenbüren, Germany
www.parsch.de info@parsch.de

Quality made in Germany ...
... Quality made by PARSCH