



Jacket:

100 % polyester high tenacity yarn, circular woven, warp threads 2-ply or 3-ply twisted, twill or plain weave

Exterior:

uncoated

Applications:

bundling of cables and wires, as protection hose for chains, ropes, steel wire ropes or hydraulic hoses, mechanical engineering, building construction, electrical and cable industry

Inner thread:

to assist with the pulling trough of objects

**JACKET N
uncoated**

multi-purpose jacket with/without inner thread



Characteristics:

abrasion resistant, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C

heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	flat width * mm	weight ** approx. g/m	wall thickness *** mm
19	3/4	30	58	1,00
25	1	41	67	1,00
32	1 1/4	53	80	1,00
38	1 1/2	60	88	1,00
42	1 2/3	66	100	1,00
45	1 3/4	70	115	1,00
52	2	82	130	1,00
64	2 1/2	101	191	1,00
70	2 3/4	110	205	1,00
75	3	118	215	1,00
90	3 1/2	141	260	1,00
102	4	159	355	1,00
110	4 1/3	171	375	1,00
125	5	194	410	1,00
152	6	237	495	1,00

* Tolerance ± 2 mm

** Tolerance ± 10 %

*** Tolerance ± 0,3 mm

