



**Inner lining:**

two-component system consisting of black SBR-rubber and white NBR-adhesive

**Jacket:**

100 % Polyester high tenacity yarn, circular woven, warp threads 4-ply twisted, twill weave

**Exterior:**

uncoated

**Applications:**

fire brigades, armed forces, technical assistance organisation

**Applicable standards:**

DIN 14811

**PARSCH SYNTHETIC 4Z SL uncoated**

fire fighting hose according to DIN 14811:2008-01+A3:2018-11 class 1 performance level 3\*\*\*



**Characteristics:**

abrasion resistant, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

**Temperature:**

cold resistant to - 30 °C  
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm	DIN approval no. **	performance level ***
42	1 2/3	248	60	30	20	1,50	ZPC 10154	3
52	2	320	60	30	20	1,60	ZPC 10155	3
75	3	540	60	30	20	1,70	ZPC 10061	3

\* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.

\*\* Issued by the central test authority for fire fighting hoses in Celle.

\*\*\* Only in conjunction with a hose cuff.

