



Inner lining:

Polyurethane lining

Jacket:

100 % Polyester high tenacity yarn, circular woven, warp threads 2-ply twisted, twill weave

Exterior:

uncoated

Applications:

fire brigades, competition hose

PARSCH FOLIANT N uncoated

Polyurethane lined fire fighting hose



Characteristics:

abrasion resistant, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm
19	3/4	80	60	30	20	1,10
25	1	100	60	30	20	1,10
32	1 1/4	120	60	30	20	1,10
38	1 1/2	140	60	30	20	1,10
42	1 2/3	160	60	30	20	1,10
45	1 3/4	165	60	30	20	1,10
52	2	200	50	25	17	1,20
64	2 1/2	270	50	25	17	1,20
70	2 3/4	330	50	25	17	1,20
75	3	370	50	25	17	1,30
90	3 1/2	440	40	20	13	1,30
102	4	500	40	20	13	1,40
110	4 1/3	560	35	18	12	1,40
125	5	640	30	15	10	1,50
152	6	710	30	15	10	1,50

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.

