



Inner lining:

Polyurethane lining

Jacket:

100 % Polyester high tenacity yarn, circular woven, warp threads 2-ply twisted, twill weave

Exterior:

Polyurethane coating

Applications:

fire brigades, competition hose

PARSCH FOLIANT COVERFLEX

Polyurethane lined fire fighting hose



Characteristics:

high abrasion resistance, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm
19	3/4	95	60	30	20	1,20
25	1	120	60	30	20	1,20
32	1 1/4	150	60	30	20	1,20
38	1 1/2	170	60	30	20	1,20
42	1 2/3	190	60	30	20	1,20
45	1 3/4	195	60	30	20	1,20
52	2	240	50	25	17	1,30
64	2 1/2	320	50	25	17	1,30
70	2 3/4	380	50	25	17	1,30
75	3	430	50	25	17	1,40
90	3 1/2	500	40	20	13	1,40
102	4	570	40	20	13	1,50
110	4 1/3	640	35	18	12	1,50
125	5	720	30	15	10	1,60
152	6	830	30	15	10	1,60

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.

