



Irrigation hoses



**Quality made in Germany ...
... Quality made by PARSCH**

PARSCH Schläuche - Armaturen GmbH & Co. KG
Gildestraße 16, 49477 Ibbenbüren, Germany
www.parsch.de



If you are looking for the perfect hose, we will be happy to help you.
As our company slogan states:

Quality made in Germany ...
... Quality made by PARSCH

our products have been used for a wide variety of applications since 1765. Please contact us for further information and advice, because not every hose is the same.

PARSCH GmbH & Co. KG
Schläuche - Armaturen
Gildestraße 16
49477 Ibbenbüren
Germany

www.parsch.de



Contact persons: International Sales



Holgar Herda

E-Mail: herda@parsch.de

Telephone: +49 (0) 5451 / 929-224



Lisa Plake

E-Mail: plake@parsch.de

Telephone: +49 (0) 5451 / 929-226

Quality made in Germany ...
... Quality made by PARSCH



Irrigation hoses

PARSCH SYNTHETIC 3Z SL, uncoated
hose according to DIN 14811

PARSCH SYNTHETIC 3Z SL, Coverflex
hose according to DIN 14811

FLORAFLEX
coated hose with a thicker inner lining

PROFI, black
fully extruded hose with ribs

PARSCH TPU
hose made of thermoplastic Polyurethane for distribution of liquid manure

TABLE OF CONTENTS



Inner lining:

two-component system consisting of black SBR-rubber and white NBR-adhesive

Jacket:

100 % Polyester high tenacity yarn, circular woven, warp threads 3-ply twisted, twill weave

Exterior:

uncoated

Applications:

irrigation hose

Applicable standards:

DIN 14811

**PARSCH SYNTHETIC 3Z SL
uncoated
irrigation hose**



Characteristics:

abrasion resistant, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm
19	3/4	110	60	30	20	1,40
25	1	140	60	30	20	1,40
32	1 1/4	175	60	30	20	1,40
38	1 1/2	200	60	30	20	1,50
42	1 2/3	240	60	30	20	1,50
45	1 3/4	250	60	30	20	1,50
52	2	310	50	25	17	1,60
64	2 1/2	410	50	25	17	1,60
70	2 3/4	470	50	25	17	1,60
75	3	520	50	25	17	1,70
90	3 1/2	620	40	20	13	1,70
102	4	700	40	20	13	1,80
110	4 1/3	790	35	18	12	1,80
125	5	930	30	15	10	1,90
152	6	1070	30	15	10	1,90

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.



Inner lining:

two-component system consisting of black SBR-rubber and white NBR-adhesive

Jacket:

100 % Polyester high tenacity yarn, circular woven, warp threads 3-ply twisted, twill weave

Exterior:

Polyurethane coating

Applications:

irrigation hose

Applicable standards:

DIN 14811

**PARSCH SYNTHETIC 3Z SL
Coverflex**

Polyurethane coated irrigation hose



Characteristics:

high abrasion resistance, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm
19	3/4	130	60	30	20	1,50
25	1	160	60	30	20	1,50
32	1 1/4	195	60	30	20	1,50
38	1 1/2	230	60	30	20	1,60
42	1 2/3	270	60	30	20	1,60
45	1 3/4	280	60	30	20	1,60
52	2	350	50	25	17	1,80
64	2 1/2	460	50	25	17	1,80
70	2 3/4	520	50	25	17	1,80
75	3	580	50	25	17	1,90
90	3 1/2	680	40	20	13	1,90
102	4	770	40	20	13	2,00
110	4 1/3	870	35	18	12	2,00
125	5	1020	30	15	10	2,10
152	6	1190	30	15	10	2,10

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.





FLORAFLEX

special hose for agriculture



Inner lining:

two-component system consisting of black SBR-rubber and white NBR-adhesive

Jacket:

100 % Polyester high tenacity yarn, circular woven, warp threads 3-ply twisted, twill weave

Exterior:

Polyurethane coating

Applications:

irrigation hose, liquid manure pumping

Characteristics:

high abrasion resistance, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C

heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	tensile strength ** kg	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm
52	2	410	55	2.800	27	18	2,00
64	2 1/2	530	55	3.200	27	18	2,00
70	2 3/4	600	55	3.500	27	18	2,00
75	3	650	55	3.800	27	18	2,00
90	3 1/2	770	50	5.600	25	17	2,40
102	4	860	50	7.200	25	17	2,40
110	4 1/3	980	45	7.500	22	15	2,40
125	5	1110	40	7.500	20	13	2,50
152	6	1260	40	8.800	20	13	2,50

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.

** The tensile strength corresponds to half of the value of the theoretical tensile strength at break.



Inner lining:

Nitril-rubber

Exterior:

Nitril-rubber with ribs

Jacket:

100 % Polyester high tenacity yarn, circular woven

Applications:

irrigation hose

PROFI

fully extruded multi-purpose layflat hose



Characteristics:

extremely high abrasion resistance, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:

cold resistant to - 30 °C

heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	tensile strength kg	tear strength kg	wall thickness mm
19	3/4	190	60	30	20	850		1,70
25	1	220	60	30	20	1000		1,70
32	1 1/4	280	60	30	20	1300		2,10
38	1 1/2	330	60	30	20	1700		2,10
42	1 2/3	350	60	30	20	1900		2,10
45	1 3/4	380	60	30	20	2000		2,30
52	2	440	50	25	17	2400		2,30
64	2 1/2	570	50	25	17	2900		2,30
70	2 3/4	620	50	25	17	3300		2,60
75	3	700	50	25	17	3900	8350	2,60
90	3 1/2	990	40	20	13	4500	9500	3,00
102	4	1120	40	20	13	5100	11200	3,00
110	4 1/3	1350	40	20	13	5500	12150	3,00
125	5	1430	30	15	10	7000	14350	3,00
152	6	1750	30	15	10	9000	18450	3,00
204	8	2500	24	12	8	12000		3,50
250	10	3000	24	12	8	16300		3,50

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.





Inner lining:

thermoplastic Polyurethane

Exterior:

thermoplastic Polyurethane

Jacket:

100 % Polyester high tenacity yarn,
circular woven

Applications:

liquid manure distribution

PARSCH TPU

layflat hose for liquid manure distribution



Characteristics:

extremely high abrasion resistance, very long service life, ageing and ozone resistant, requires no drying after use

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter mm	inner diameter inch	weight approx. g/m	burst pressure bar	working pressure * bar (2:1)	working pressure * bar (3:1)	wall thickness mm	tear strength kg
102	4	900	50	25	17	3,50	16.000
115	4 1/2	1000	40	20	13	3,50	18.500
125	5	1700	40	20	13	3,50	19.800
152	6	2000	40	20	13	3,80	27.000
204 **	8	3000	40	20	13	3,80	36.000

* Maximum recommended working pressure of the hose or maximum working pressure of the attached couplings whichever is the lower.

** Available in black only



Quality made in Germany ...
... Quality made by PARSCH



PARSCH Schläuche - Armaturen GmbH & Co. KG
Gildestraße 16, 49477 Ibbenbüren, Germany
www.parsch.de