



Aeration hoses



**Quality made in Germany ...
... Quality made by PARSCH**

PARSCH Schläuche - Armaturen GmbH & Co. KG
Gildestraße 16, 49477 Ibbenbüren, Germany
www.parsch.de



If you are looking for the perfect hose, we will be happy to help you.
As our company slogan states:

Quality made in Germany ...
... Quality made by PARSCH

our products have been used for a wide variety of applications since 1765. Please contact us for further information and advice, because not every hose is the same.

PARSCH GmbH & Co. KG
Schläuche - Armaturen
Gildestraße 16
49477 Ibbenbüren
Germany

www.parsch.de



Contact persons: International Sales



Holgar Herda

E-Mail: herda@parsch.de

Telephone: +49 (0) 5451 / 929-224



Lisa Plake

E-Mail: plake@parsch.de

Telephone: +49 (0) 5451 / 929-226

Quality made in Germany ...
... Quality made by PARSCH



Aeration hoses

SILOFLEX N, uncoated

special hose for the aeration of bulk powders and granular

SILOFLEX, one side yellow Polyurethane coated

special hose for the aeration of bulk powders and granular

TABLE OF CONTENTS



Jacket:

100 % Polyester high tenacity yarn, circular woven, special plain weave with two red warp threads with defined air permeability

Applications:

aeration and discharge of bulk powders and granular in silos and silo wagons

Air permeability:

tested according to DIN EN ISO 9237 (DIN 53887)
test surface: 20 cm²

inlet pressure bar	liter/m ² x second
0,01	approx. 3,8
0,02	approx. 5,6
0,03	approx. 5,9

inner diameter mm	inner diameter inch	flat width mm	weight approx. g/m	tensile strength * kg
52	2	84	160	2.200
71		113	210	3.000
75	3	120	240	3.200

* The tensile strength corresponds to half of the value of the theoretical tensile strength at break.

**SILOFLEX N
uncoated**

special hose for the aeration of bulk powders and granular



Characteristics:

one side air permeable, lightweight and flexible, good abrasion resistance, anti-rot construction

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)





SILOFLEX

special hose for the aeration of bulk powders and granular



Jacket:

100 % Polyester high tenacity yarn, circular woven, special plain weave with two red warp threads with defined air permeability

Exterior:

one side Polyurethane coated

Applications:

aeration and discharge of bulk powders and granular in silos and silo wagons

Air permeability:

tested according to DIN EN ISO 9237 (DIN 53887)
test surface 20 cm²

inlet pressure bar	liter/m ² x second
0,01	approx. 3,8
0,02	approx. 5,6
0,03	approx. 5,9

Characteristics:

one side air permeable, lightweight and flexible, good abrasion resistance, anti-rot construction

Temperature:

cold resistant to - 30 °C
heat resistant up to + 100 °C (temporarily higher)

inner diameter* mm	inner diameter inch	flat width mm	weight approx. g/m	tensile strength ** kg
52	2	84	160	3.200
71		113	210	3.000
75	3	120	240	3.200

* Standard diameter 71 mm, other diameters on request.

** The tensile strength corresponds to half of the value of the theoretical tensile strength at break.

Quality made in Germany ...
... Quality made by PARSCH



PARSCH Schläuche - Armaturen GmbH & Co. KG
Gildestraße 16, 49477 Ibbenbüren, Germany
www.parsch.de